

"We Care About You & Your Property" (561)742-7222 www.InspectionXpress.com



Client: Grand Isles Condominium

Address: 4151 Haverhill Rd City West Palm Beach

Inspector: Bryan Larsen License #: Hi13470

Inspection Xpress

2005 Vista Parkway, Suite 200, West Palm Beach, FL 33411 Phone 561-742-7222 - Fax 888-688-9696

> <u>www.inspectionxpress.com</u> contact@inspectionxpress.com



"We Care About You & Your Property" (561)742–7222

www.inspectionxpress.com





LICENSE



WIND MITIGATION CERTIFICATION

No Sketch Image Available

AERIAL VIEW

STRUCTURAL DETAIL

Inspection Xpress

2005 Vista Parkway, Suite 200 West Palm Beach, FL 33411 561-742-7222

contact@inspectionsxpress.com
www.inspectionxpress.com



Uniform Mitigation Verification Inspection Form Maintain a copy of this form and any documentation provided with the insurance policy

	Instruction Date: 04/04/0004							
Inspection Date: 04/04/2024								
Owner Information Owner Name: Grand Isles Condominium Contact Person:								
Address:4151 Haverhill Rd	wner Name:Grand Isles Condominium							
			Home Phone: Work Phone:					
City:West Palm Beach County: Palm Beach	Zip: 33417		Work Phone: Cell Phone:					
Insurance Company:								
* *			Policy #: Email:					
Year of Home:2000	# of Stories	:	Eman:					
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.								
Building Code: Was the structure built the HVHZ (Miami-Dade or Broward co	unties), South	Florida Building Code (SFBC-9	4)?					
A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)								
B. For the HVHZ Only: Built in cor								
provide a permit application with a		•	on Date (MM/DD/YYYY)					
✓ C. Unknown or does not meet the re	1							
2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.								
Permit 2.1 Roof Covering Type:	Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance				
1. Asphalt/Fiberglass Shingle								
2. Concrete/Clay Tile	2023	#23030353	2023					
3. Metal	/							
4. Built Up	/							
5. Membrane/	/			Ħ				
6. Other				Ħ				
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.								
B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.								
C. One or more roof coverings do not meet the requirements of Answer "A" or "B".								
D. No roof coverings meet the requirements of Answer "A" or "B".								
3. Roof Deck Attachment: What is the weakest form of roof deck attachment?								
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.								
B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.								
24"inches o.c.) by 8d common nails decking with a minimum of 2 nails Any system of screws, nails, adhesi	24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent							
Inspectors Initials BL Property Address 4151 Haverhill Rd								

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4



or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.							
	Reinforced Concrete Roof Deck.						
_	Other:						
_	Jnknown or unidentified.						
G. 1	No attic access.						
	<u>Wall Attachment</u> : What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within the inside or outside corner of the roof in determination of WEAKEST type)						
A. 7	Toe Nails						
	Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or						
	Metal connectors that do not meet the minimal conditions or requirements of B, C, or D						
Minimal	l conditions to qualify for categories B, C, or D. All visible metal connectors are:						
	Secured to truss/rafter with a minimum of three (3) nails, and						
	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.						
✓ B. 0	Clips						
	✓ Metal connectors that do not wrap over the top of the truss/rafter, or						
	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.						
☐ C. S	Single Wraps						
	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side. Double Wraps						
<i>D</i> . 1	Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or						
	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.						
	Structural Anchor bolts structurally connected or reinforced concrete roof. Other:						
☐ G. U	Unknown or unidentified						
H. N	No attic access						
	cometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).						
✓ A. I	Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: feet						
☐ B. F	Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of						
C. (less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft Other Roof Any roof that does not qualify as either (A) or (B) above.						
6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss.							
∐ В. №	No SWR.						
✓ C. U	Unknown or undetermined.						
Inspectors 1	Initials BL Property Address 4151 Haverhill Rd						

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.



7. <u>Opening Protection</u>: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed Openings								Non-Glazed Openings		
openi form	ace an "X" in each row to identify all forms of protection in use for each pening type. Check only one answer below (A thru X), based on the weakest orm of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Windows or Entry Doors		Garage Doors		Skylights		ass ock	Entry Doors	Garage Doors		
N/A	Not Applicable- there are no openings of this type on the structure				X		X	X	1				
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)			Ť	Ť			╁	П				
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)		T	Ħ			\Box		П				
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007			\top							\sqcap		
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance												
N	Opening Protection products that appear to be A or B but are not verified	$oxed{oxed}$	_	$\perp \downarrow$			Ш	$\bot\!$	Ш				
	Other protective coverings that cannot be identified as A, B, or C	LĻ.		$\perp \downarrow$			Ш	1	Ш				
Х	No Windborne Debris Protection								Ш				
a	nd Large Missile Impact" (Level A in the table above). • Miami-Dade County PA 201, 202, <u>and</u> 203												
	 Florida Building Code Testing Application Standard (TAS) 20 	1, 202	2, <u>an</u>	<u>d</u> 203									
	 American Society for Testing and Materials (ASTM) E 1886 a 	and A	STM	E 19	96								
	 Southern Standards Technical Document (SSTD) 12 												
	• For Skylights Only: ASTM E 1886 and ASTM E 1996												
	 For Garage Doors Only: ANSI/DASMA 115 												
	A.1 All Non-Glazed openings classified as A in the table above, or no Non-G	lazed	open	ings (exist								
	A.2 One or More Non-Glazed openings classified as Level D in the table abo X in the table above	ve, an	d no	Non-	Glaze	d op	enings	class	sifie	d as Leve	el B, C, N		
	A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in	n the t	able	above									
o ir	s. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb L penings are protected, at a minimum, with impact resistant coverings in the product approval system of the State of Florida or Miami-Dade Cor "Cyclic Pressure and Large Missile Impact" (Level B in the table ab	or pro	oducty and	ts list	ed as	s wi	ndbor	ne d	ebris	protec	tion dev		
	• ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.)												
	• SSTD 12 (Large Missile – 4 lb. to 8 lb.)												
	• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large	Miss	ile - 2	2 to 4.	5 lb.))							
	B.1 All Non-Glazed openings classified as A or B in the table above, or no N	on-Gl	azed	openi	ngs e	xist							
	B.2 One or More Non-Glazed openings classified as Level D in the table above	ve, an	d no l	Non-	Glaze	d op	enings	class	sified	l as Leve	el C, N, o		
	B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the	e table	e abo	ve									
	Exterior Opening Protection- Wood Structural Panels meeting ywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 20								ings	are co	overed v		
	C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no												
F	C.2 One or More Non-Glazed openings classified as Level D in the table aborthe table above							class	sified	l as Leve	el N or X		
L	the table above												
	C.3 One or More Non-Glazed openings is classified as Level N or X in the tal	ble ab	ove										
	-	ble ab	ove										

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Inspection Xpress 561-742-7222 Page 3 of 4
Email: contact@inspectionxpress.com



N. Exterior Opening Protection (unverified shutter systems with no documentation) All Glazed openings are protected with protective coverings not meeting the requirements of Answer "A", "B", or C" or systems that appear to meet Answer "A" or "B"							
with no documentation of compliance (Level N in the table above).							
N.1 All Non-Glazed openings classified as Level A, B, C, o	or N in the table above, or no No	on-Glazed openings exist					
N.2 One or More Non-Glazed openings classified as Level table above	D in the table above, and no No	on-Glazed openings classified as Level X in the					
N.3 One or More Non-Glazed openings is classified as Lev							
X. None or Some Glazed Openings One or more Glaz	ed openings classified and L	evel X in the table above.					
MITIGATION INSPECTIONS MUST BE CERTIFIED BY A QUALIFIED INSPECTOR. Section 627.711(2), Florida Statutes, provides a listing of individuals who may sign this form.							
Qualified Inspector Name:	License Type:	License or Certificate #:					
Bryan Larsen Inspection Company:	Home Inspect	Hi13470					
Inspection Xpress		561-742-7222					
Qualified Inspector – I hold an active license as a	· (check one)	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
	' '	arrangahan afhayna afhyrmiaana mitigation					
training approved by the Construction Industry Licensing Board	and completion of a proficiency						
Building code inspector certified under Section 468.607, Florida	Statutes.						
General, building or residential contractor licensed under Section							
Professional engineer licensed under Section 471.015, Florida S	tatutes.						
Professional architect licensed under Section 481.213, Florida Statutes.							
Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.							
Individuals other than licensed contractors licensed under	Section 489.111, Florida St	tatutes, or professional engineer licensed					
under Section 471.015, Florida Statues, must inspect the st							
Licensees under s.471.015 or s.489.111 may authorize a dir	ect employee who possesses	s the requisite skill, knowledge, and					
experience to conduct a mitigation verification inspection.							
I, Bryan Larsen am a qualified inspector and I personally performed the inspection or (licensed (print name)							
contractors and professional engineers only) I had my employee () perform the inspection (print name of inspector)							
and-I agree to be responsible for lister work.							
Qualified Inspector Signature: Date: 04/04/2024							
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is							
subject to investigation by the Florida Division of Insurance	e Fraud and may be subject	et to administrative action by the					
appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who							
certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally							
performed the inspection.							
Homeowner to complete: I certify that the named Qualifie residence identified on this form and that proof of identification							
		•					
Signature:	Date:	_					
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to							
obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)							
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.							
4151 Haverhill Rd Inspectors Initials BL Property Address							
*This verification form is valid for un to five (5) years provided no material changes have been made to the structure or							

inaccuracies found on the form.

INSPECTION XPRESS



Address



Right Elevation



Left Elevation



Front Elevation



Rear Elevation



Unprotected Opening


INSPECTION XPRESS



Unprotected Opening



8d nail



Roof Permit



Clip



6x6 nail spacing

