

"We Care About You & Your Property"
(561)742-7222
www.InspectionXpress.com



Client: Grand Isles Condominium

Address: 4167 Haverhill Rd City West Palm Beach

Inspector: Bryan Larsen License #: Hi13470

Inspection Xpress

2005 Vista Parkway, Suite 200, West Palm Beach, FL 33411 Phone 561-742-7222 - Fax 888-688-9696

> <u>www.inspectionxpress.com</u> contact@inspectionxpress.com



"We Care About You & Your Property" (561)742–7222

www.inspectionxpress.com





LICENSE



WIND MITIGATION CERTIFICATION

No Sketch Image Available

AERIAL VIEW

STRUCTURAL DETAIL

Inspection Xpress

2005 Vista Parkway, Suite 200 West Palm Beach, FL 33411 561-742-7222

contact@inspectionsxpress.com
www.inspectionxpress.com



Uniform Mitigation Verification Inspection Form Maintain a copy of this form and any documentation provided with the insurance policy

	Instruction Date: 0.4/44/0004									
Inspection Date: 04/11/2024										
Owner Name: Owner delay Consideration			Contact Person:							
	ner Name:Grand Isles Condominium									
	Address:4167 Haverhill Rd		Home Phone: Work Phone:							
City:West Palm Beach County: Palm Beach	Zip: 33417		Cell Phone:							
Insurance Company:			Policy #:							
* *			Email:							
Year of Home:2000	# of Stories	:	Eman:							
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.										
Building Code: Was the structure built the HVHZ (Miami-Dade or Broward co	unties), South	Florida Building Code (SFBC-9	4)?							
A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)										
B. For the HVHZ Only: Built in cor										
provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)										
<u> </u>	1									
2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.										
Permit 2.1 Roof Covering Type:	Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance						
1. Asphalt/Fiberglass Shingle	/									
2. Concrete/Clay Tile	2023	#23030353	2023							
3. Metal	/									
4. Built Up	/									
5. Membrane/	/			Ħ						
6. Other				Ħ						
A. All roof coverings listed above n installation OR have a roofing perm										
B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.										
C. One or more roof coverings do not meet the requirements of Answer "A" or "B".										
D. No roof coverings meet the requirements of Answer "A" or "B".										
3. Roof Deck Attachment: What is the weakest form of roof deck attachment?										
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.										
24"inches o.c.) by 8d common nails other deck fastening system or truss	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.									
C. Plywood/OSB roof sheathing wi 24"inches o.c.) by 8d common nails decking with a minimum of 2 nails Any system of screws, nails, adhesi	s spaced a ma per board (or ives, other dec	ximum of 6" inches in the field. 1 nail per board if each board is kk fastening system or truss/rafte	-OR- Dimensional lumber equal to or less than 6 in	er/Tongue & Groove ches in width)OR-						
Inspectors Initials BL Property Addre	ss416/ Have	rniii Ka								

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4



or greater resistance than 8d common nails space 182 psf.	d a maximum of 6 inches in the field or has a mean uplift resistance of at least
D. Reinforced Concrete Roof Deck.	
E. Other:	
F. Unknown or unidentified.	
G. No attic access.	
4. Roof to Wall Attachment: What is the WEAKEST 5 feet of the inside or outside corner of the roof in det	roof to wall connection? (Do not include attachment of hip/valley jacks within ermination of WEAKEST type)
A. Toe Nails	
Truss/rafter anchored to top plate the top plate of the wall, or	of wall using nails driven at an angle through the truss/rafter and attached to
Metal connectors that do not meet	the minimal conditions or requirements of B, C, or D
Minimal conditions to qualify for categories B, C,	or D. All visible metal connectors are:
Secured to truss/rafter with a mining	num of three (3) nails, and
	e wall framing, or embedded in the bond beam, with less than a ½" gap from ocked no more than 1.5" of the truss/rafter, and free of visible severe
✓ B. Clips	
✓ Metal connectors that do not wrap	over the top of the truss/rafter, or
position requirements of C or D, b	of 1 strap that wraps over the top of the truss/rafter and does not meet the nail at is secured with a minimum of 3 nails.
C. Single Wraps	-i1
	single strap that wraps over the top of the truss/rafter and is secured with a de and a minimum of 1 nail on the opposing side.
Metal Connectors consisting of 2 s beam, on either side of the truss/ra	eparate straps that are attached to the wall frame, or embedded in the bond fter where each strap wraps over the top of the truss/rafter and is secured with side, and a minimum of 1 nail on the opposing side, or
	ngle strap that wraps over the top of the truss/rafter, is secured to the wall on p plate with a minimum of three nails on each side.
E. Structural Anchor bolts structurally conr F. Other:	ected or reinforced concrete roof.
G. Unknown or unidentified	
H. No attic access	
	sider roofs of porches or carports that are attached only to the fascia or wall of ination of roof perimeter or roof area for roof geometry classification).
	apes greater than 10% of the total roof system perimeter. es: feet; Total roof system perimeter: feet
	nore units where at least 90% of the main roof area has a roof slope of
C. Other Roof C. Other Roof	slope less than 2:12 sq ft; Total roof area sq ft as either (A) or (B) above.
A. SWR (also called Sealed Roof Deck) Self-add	erlayments or hot-mopped felts do not qualify as an SWR) nering polymer modified-bitumen roofing underlayment applied directly to the foamed-on insulation) applied as a supplemental means to protect the roof covering loss.
B. No SWR.	
C. Unknown or undetermined.	
Inspectors Initials BL Property Address 4167 Have	rhill Rd

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.



7. <u>Opening Protection</u>: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed Openings									Non-Glazed Openings		
openi form (ace an "X" in each row to identify all forms of protection in use for each pening type. Check only one answer below (A thru X), based on the weakest orm of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Windows or Entry Doors Garage			S	Skylights		Glass Block		Entry Doors	Garage		
N/A	Not Applicable- there are no openings of this type on the structure			1	∇		∇		∇	1	ΙП			
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)		\dashv	╁	\mathcal{L}		\vdash	\vdash	\cap	-	╟┼┼			
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/4:5 lb for skylights)		\dashv	╁	╁		╁	\vdash	\vdash	-	╟┼┼	\vdash		
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007	\vdash	\dashv	╁	╁		\vdash	\vdash	Н	-	$\vdash\vdash\vdash$	Н		
	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E	-					-		ш		H	╁┸		
D	330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance			L,								<u> </u>		
N	Opening Protection products that appear to be A or B but are not verified			ot			Ш							
	Other protective coverings that cannot be identified as A, B, or C			Ш	_		Ш	Ш						
Х	No Windborne Debris Protection		<u> </u>									X		
	 Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 20 			_										
	American Society for Testing and Materials (ASTM) E 1886			_										
	Southern Standards Technical Document (SSTD) 12													
	• For Skylights Only: ASTM E 1886 and ASTM E 1996													
	For Garage Doors Only: ANSI/DASMA 115													
	A.1 All Non-Glazed openings classified as A in the table above, or no Non-C	ilazed	l openi	ings	exist									
	A.2 One or More Non-Glazed openings classified as Level D in the table abo X in the table above		-	_		ed o	penin	ıgs c	lassi	fied	as Leve	el B, C, N		
	A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X i	n the	table a	abov	2									
$\exists B$	Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb I	arge	e Mis	sile	(2-4	.5 I	b fo	r sk	vlig	hts	only)	All Gla		
op in	benings are protected, at a minimum, with impact resistant coverings the product approval system of the State of Florida or Miami-Dade Or "Cyclic Pressure and Large Missile Impact" (Level B in the table ab	or pr Count	oduct ty and	s lis	ted a	s w	indb	orne	del	oris	protec	tion dev		
	• ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.)	,												
	• SSTD 12 (Large Missile – 4 lb. to 8 lb.)													
	• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large	Miss	sile - 2	to 4	.5 lb.)								
	B.1 All Non-Glazed openings classified as A or B in the table above, or no N													
	B.2 One or More Non-Glazed openings classified as Level D in the table abo in the table above			_	-			gs c	lassi	fied	as Leve	el C, N, o		
	B.3 One or More Non-Glazed openings is classified as Level C, N, or X in th	e tabl	le abov	/e										
<u>C.</u>	Exterior Opening Protection- Wood Structural Panels meeting wood/OSB meeting the requirements of Table 1609.1.2 of the FBC 20	ng F	BC 2	200′						ngs	are co	overed		
17	C.1 All Non-Glazed openings classified as A, B, or C in the table above, or n							-	/					
_	C.2 One or More Non-Glazed openings classified as Level D in the table abo				-	-		gs c	lassi	fied	as Leve	l N or X		
	the table above													
	the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the ta	ble ab	oove											
necto	1	ble ab	oove											

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Inspection Xpress 561-742-7222 Page 3 of 4
Email: contact@inspectionxpress.com



N. Exterior Opening Protection (unverified shutter protective coverings not meeting the requirements of A	answer "A", "B",	documentation) All or C" or systems that	Il Glazed openings are protected with at appear to meet Answer "A" or "B"					
with no documentation of compliance (Level N in the ta	able above).							
N.1 All Non-Glazed openings classified as Level A, B, C,	or N in the table ab	ove, or no Non-Glazeo	d openings exist					
N.2 One or More Non-Glazed openings classified as Level table above	D in the table above	ve, and no Non-Glazed	d openings classified as Level X in the					
N.3 One or More Non-Glazed openings is classified as Lev								
X. None or Some Glazed Openings One or more Glaz	red openings clas	sified and Level X is	n the table above.					
MITIGATION INSPECTIONS MUST I Section 627.711(2), Florida Statutes, prov		~						
Qualified Inspector Name:	License Type:		License or Certificate #:					
Bryan Larsen Inspection Company:	Home I	nspector Phone:	Hi13470					
Inspection Ynress		5	61-742-7222					
Qualified Inspector – I hold an active license as a	a: (check one)							
Home inspector licensed under Section 468.8314, Florida Statut training approved by the Construction Industry Licensing Board			per of hours of hurricane mitigation					
Building code inspector certified under Section 468.607, Florida	a Statutes.							
General, building or residential contractor licensed under Section	on 489.111, Florida	Statutes.						
Professional engineer licensed under Section 471.015, Florida Statutes.								
Professional architect licensed under Section 481.213, Florida Statutes.								
Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.								
Individuals other than licensed contractors licensed under	Section 489.111	, Florida Statutes,	or professional engineer licensed					
under Section 471.015, Florida Statues, must inspect the st	tructures person	ally and not throug	gh employees or other persons.					
Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and								
experience to conduct a mitigation verification inspection.								
I, Bryan Larsen am a qualified inspector and I personally performed the inspection or (licensed (print name)								
contractors and professional engineers only) I had my employee () perform the inspection								
	(b	rint name of inspe	ctor)					
and-I agree to be responsible for his/her work.								
Qualified Inspector Signature: Date: 04/11/2024								
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the								
appropriate licensing agency or to criminal prosecution. (S								
certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally								
performed the inspection.								
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification								
Signature:	Data							
Signature.	Date:		Z					
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)								
The definitions on this form are for inspection purposes or as offering protection from hurricanes.	•	e used to certify an	y product or construction feature					
Inspectors Initials BL Property Address 4167 Haverhill Rd								
*This varification form is valid for up to five (5) years prov	vidad na matavi	al ahangas haya bas	on made to the structure or					

This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

INSPECTION XPRESS



Address



Right Elevation



Left Elevation



Front Elevation



Rear Elevation



Unprotected Opening


INSPECTION XPRESS



Unprotected Opening



8d nail



Roof Permit



Clip



6x6 nail spacing

